

Approved/Notes

Customer

Project

Job#

PA Insert Quote/Order#

Ship Date

Page _____ of _____

Fax to:

Fax#

From

Date

2 3/8"

A

Frame Opening

B

Frame Opening

Stiffeners (as required)

S.S. Pneumatic Assist (as req'd)

Stainless Steel Hinges

Automatic, Aluminum Hold Open Arm w/Red Release Handle

Stainless Steel Snap/Slam Lock

Removable "T" Handle for Slam Lock

Continuous Neoprene Gasket

Automatic, Aluminum Hold Open Arm with Red Release Handle

S.S. Pneumatic Assist (as req'd)

Double Leaf Drip Channel

"Just Set" ALUMINUM DOOR, STANDARD DUTY, DOUBLE LEAF - NON-WATERTIGHT

- 1/4" Diamond Plate Lid Reinforced for 300 lb/ft² live load
- 6" Frame (typ) with Gasket
- Protective Barrier where Concrete meets Aluminum
- Stainless Steel Pneumatic Assist (as req'd)
- Aluminum Hinge with S.S. Hinge Pin
- Stainless Steel Hardware
- Type 316 Stainless Steel Snap Lock
- Automatic Hold Open Arm with Red Release Handle
- Flush Mounted Lift Handle

STANDARD DIMENSIONS				
QTY	A	B	C	STOCK#
	30"	48"	6.00"	AYS3048D
	36"	48"	6.00"	AYS3648D
	48"	48"	6.00"	*AYS4848D
	48"	72"	6.00"	*AYS4872D
	60"	60"	6.00"	*AYS6060D

An asterisk (*) next to stock number = stainless steel pneumatic assist is standard.

Installation shall be in accordance with manufacturer's instructions

NO SCALE

12/08