



Specifications

- **Material:** Aluminum cover and extruded aluminum frame.
- **Cover:** Diamond-pattern tread plate reinforced for 300 psf (1464 kg/m²) live load.
- **Frame:** Extruded aluminum channel frame with anchor flanges around the perimeter. A 1-1/2" (38mm) PVC drain coupling is attached to the drip channel frame for a pipe connection to a dry well or disposal system. Gasket in frame for water resistance.
- **Hinges:** Heavy duty Type 304 stainless steel hinges.
- **Latch:** Type 316 stainless steel slam lock with fixed interior handle and removable exterior turn/lift handle. Latch release is protected by a flush, gasketed, removable screw plug.
- **Lift Assistance:** Stainless Steel spring assist on some models *. (Compression gas spring optional). Aluminum hold-open arm automatically locks cover in the open position.
- **Finish:** Mill Finish aluminum with a electrolytic barrier applied to the exterior of the frame.
- **Hardware:** Type 304 stainless steel throughout except where noted.

PART #	DIM "A"	DIM "B"
AWS3048D	30"	48"
AWS3648D	36"	48"
AWS3660D *	36"	60"
AWS4848D *	48"	48"
AWS4872D *	48"	72"
AWS6060D *	60"	60"

Models with * receive assist